


# Desktop ISO14443A Protocol HF Tag Reader



**Model: RR1036CF**

**Size: 83mmx43mmx11.6mm/15.2mm**

**Weight: 50g**

## GENERAL DESCRIPTION

RR1036CF is a high performance ISO14443A Protocol HF tag reader. It is designed upon fully self-intellectual property and supports fast tag read/write operation with high identification rate. It can be widely applied in many RFID application systems such as logistics, personnel identification, conference attendance system, access control, anti-counterfeit and industrial production process control system.

## FEATURES

- Self-intellectual property;
- Support ISO14443A protocol tag;
- Advanced tag processing algorithm, high identification rate;
- Built-in TX/RX antenna with effective distance up to 70mm<sup>\*</sup>;
- CF II interface. No external power source needed;
- Provide DLL and demonstration software to facilitate development.

## CHARACTERISTICS

- Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	3.3	V
Operating Temp.	T <sub>OPR</sub>	-10~+60	°C
Storage Temp.	T <sub>STR</sub>	-25~+80	°C

- Electrical and Mechanical Specification

Under T<sub>A</sub>=25°C, VCC=+3.3V unless specified

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	3.0	3.3	3.6	V
Current Dissipation	I <sub>C</sub>		45	65	mA
Frequency	F <sub>REQ</sub>		13.56		MHz
Effective Distance <sup>*</sup>	DIS	0	50	70	mm

<sup>\*</sup>Effective distance depends on tag and working environment.

Remark:

1. Specifications are subject to change, please pay attention to our latest one.
2. Shenzhen RoyalRay Science and Technology Co., Ltd. reserves the right to the final interpretation of the above terms.